


95966A211

Panel Screws

Captive Panel Screws

Use these nonmagnetic screws for panel assemblies, cabinets, and enclosures. They also work well as instrument hardware and as needle valves in pneumatic tools. Made of 18-8 passivated stainless steel, screws can be held captive in panels with retainers (sold separately below). Screws meet ASTM-A581-A582. Length is measured from under head.

Also Available: Springs to provide preload and even compression on panels. Please ask for spring 9435K12 for No. 2 diameter; spring 9435K24 for No. 4 and No. 6 diameters; spring 9435K36 for No. 8 and No. 10 diameters; spring 9435K5 for 1/4" diameter; and 94125K472 for M3, M3.5, and M4 diameters.



Knurled Head Panel Screws

Lg.	Each*	Lg.	Each*	Lg.	Each*	Lg.	Each*	Lg.	Each*
4-40	Thread Lg.: 1/8"	6-32 (Cont.)		10-24 (Cont.)		10-32 (Cont.)		1/4"-20 (Cont.)	
	Head: Dia. 1/4"; Ht. 1/4"	7/8" 91035A360 \$4.28		5/8" 91035A460 \$4.89		3/4" 91035A530 \$5.86		1"	91035A625 \$10.29
3/8"	91035A190 \$3.18	1" 91035A370 5.97		3/4" 91035A470 5.87		7/8" 91035A540 6.03		1 1/4"	91035A640 11.75
1/2"	91035A210 3.79	8-32	Thread Lg.: 1/32"	1/8" 91035A480 5.81		1" 91035A550 6.28		1 1/2"	91035A650 9.47
5/8"	91035A220 4.16		Head: Dia. 5/16"; Ht. 5/16"	1/8" 91035A490 6.29		1 1/8" 91035A570 6.73		1/4"-28	Thread Lg.: 3/16"
3/4"	91035A230 5.11	1/2"	91035A390 \$4.11	1/8" 91035A495 6.73		1 1/4" 91035A590 7.86			Head: Dia. 1/2"; Ht. 9/16"
7/8"	91035A240 4.59	5/8"	91035A400 4.16	1/4" 91035A497 7.34		1 3/8" 91035A593 7.95		5/8"	91035A710 \$7.95
1"	91035A250 5.30	3/4"	91035A410 5.43	1/2" 91035A499 7.95		1 1/2" 91035A595 8.20		3/4"	91035A730 8.56
6-32	Thread Lg.: 1/32"	7/8"	91035A420 4.89	1 3/8" 91035A501 11.26		1/4"-20	Thread Lg.: 5/16"	1"	91035A750 12.75
	Head: Dia. 5/16"; Ht. 5/16"	1"	91035A430 5.68	10-32	Thread Lg.: 1/4"		Head: Dia. 1/2"; Ht. 9/16"	1 1/4"	91035A770 13.18
1/2"	91035A330 \$3.90	10-24	Thread Lg.: 1/4"		Head: Dia. 3/8"; Ht. 7/16"	5/8" 91035A610 \$8.69		1 1/2"	91035A790 15.88
5/8"	91035A340 4.61		Head: Dia. 3/8"; Ht. 7/16"	1/2" 91035A510 \$5.45		3/4" 91035A615 9.07		1 3/4"	91035A810 17.25
3/4"	91035A350 4.41	1/2"	91035A450 \$5.46	5/8" 91035A508 5.61		7/8" 91035A620 9.46			

Fillister Head Panel Screws


Lg.	Each*	Lg.	Each*	Lg.	Each*	Lg.	Each*	Lg.	Each*
4-40	Thread Lg.: 3/16"	6-32	Thread Lg.: 1/32"	8-32	Thread Lg.: 1/32"	10-24	Thread Lg.: 9/32"	10-32	Thread Lg.: 9/32"
	Head: Dia. 11/64"; Ht. 0.107"		Head: Dia. 1/32"; Ht. 0.132"		Head: Dia. 1/4"; Ht. 0.156"		Head: Dia. 5/16"; Ht. 0.180"		Head: Dia. 5/16"; Ht. 0.180"
1/2"	94375A320 \$2.57	1/2"	94375A405 \$2.63	1/2"	94375A520 \$3.10	1/2"	94375A615 \$2.75	1/2"	94375A715 \$2.75
3/4"	94375A340 3.82	3/4"	94375A425 2.90	3/4"	94375A540 3.25	3/4"	94375A635 4.53	3/4"	94375A735 4.50
		1"	94375A445 4.21	1"	94375A560 3.36	1"	94375A655 4.78	1"	94375A755 4.74

Metric Knurled Head Panel Screws

Lg., mm	Each*	Lg., mm	Each*	Lg., mm	Each*
M3	Pitch: 0.50 mm; Thread Lg.: 3.2 mm Head Dia. and Ht.: 6.5 mm	M3.5	Pitch: 0.60 mm; Thread Lg.: 5.5 mm Head Dia. and Ht.: 8.0 mm	M4	Pitch: 0.70 mm; Thread Lg.: 5.5 mm Head Dia. and Ht.: 8.0 mm
11	95536A113 \$7.51	11	95536A207 \$8.79	11	95536A305 \$8.79
13	95536A127 7.59	13	95536A215 9.00	13	95536A318 9.00
14.5	95536A141 7.68	14.5	95536A223 9.08	14.5	95536A331 9.08
17.5	95536A155 10.35	17.5	95536A231 11.84	17.5	95536A344 11.84
22	95536A169 10.57	22	95536A239 12.18	22	95536A357 12.18

Captive Large Diameter Hex Socket Head Panel Screws


These screws have a larger head diameter than other captive panel screws. Made of 18-8 passivated stainless steel, screws can be held captive in panels with retainers (sold separately below).



Lg.	Each*	Lg.	Each*	Lg.	Each*	Lg.	Each*
4-40	Thread Lg.: 3/16"	6-32	Thread Lg.: 1/32"	8-32	Thread Lg.: 1/4"	10-32	Thread Lg.: 5/16"
	Head: Dia. 1/4"; Ht. 1/8"		Head: Dia. 9/32"; Ht.: 1/8"		Head: Dia. 5/16"; Ht.: 5/32"		Head: Dia. 3/8"; Ht.: 3/16"
	Hex Size: 3/64"		Hex Size: 3/64"		Hex Size: 1/16"		Hex Size: 1/16"
1 3/32"	96050A217 \$3.42	1 7/32"	96050A229 \$3.97	2 1/32"	96050A257 \$4.92	2 7/32"	96050A289 \$5.61
1 1/2"	96050A223 3.69	1 9/32"	96050A235 4.24	2 3/32"	96050A269 5.19	2 9/32"	96050A295 6.02
		2 1/32"	96050A246 4.65	2 5/32"	96050A278 5.33		

Captive Hex Socket/Knurled Head Panel Screws

The combination hex socket/knurled head lets you tighten these screws easily by wrench or hand. Made of 18-8 passivated stainless steel, screws can be held captive in panels with retainers (sold separately below).



Lg.	Each*	Lg.	Each*	Lg.	Each*	Lg.	Each*	Lg.	Each*
4-40	Thread Lg.: 5/32"	6-32 (Cont.)		8-32 (Cont.)		10-32 (Cont.)		1/4"-20 (Cont.)	
	Head: Dia. 11/64"; Ht. 0.112"	1/2"	95966A221 \$3.69	1"	95966A341 \$3.83	1 1/2"	95966A445 \$4.65	2"	95966A549 \$6.49
	Hex Size: 3/32"	9/16"	95966A226 3.76			1 3/4"	95966A449 4.72	5/16"-18	Thread Lg.: 3/16"
1/4"	95966A121 \$3.42	5/8"	95966A231 3.83	10-32	Thread Lg.: 1/4"		Head: Dia. 1 5/32"; Ht. 0.190"		Head: Dia. 1 5/32"; Ht. 0.312"
5/16"	95966A125 3.56	3/4"	95966A237 3.89		Head: Dia. 5/16"; Ht. 0.190"		Hex Size: 5/32"		Hex Size: 1/4"
3/8"	95966A130 3.69	1"	95966A239 3.97	1/2"	95966A410 \$4.10		Hex Size: 3/16"		Hex Size: 3/16"
7/16"	95966A135 3.76	8-32	Thread Lg.: 3/16"	9/16"	95966A414 4.17		Hex Size: 5/16"		Hex Size: 5/16"
1/2"	95966A140 3.83		Head: Dia. 1 7/64"; Ht. 0.164"	5/8"	95966A419 4.24		Hex Size: 3/8"		Hex Size: 3/8"
5/8"	95966A145 3.83	1/2"	95966A316 \$3.69	3/4"	95966A423 4.31		Hex Size: 1/2"		Hex Size: 1/2"
6-32	Thread Lg.: 3/16"	9/16"	95966A323 3.69	1"	95966A428 4.38		Hex Size: 5/8"		Hex Size: 5/8"
	Head: Dia. 7/32"; Ht. 0.138"	5/8"	95966A329 3.56	7/8"	95966A432 4.44		Hex Size: 3/4"		Hex Size: 3/4"
	Hex Size: 7/64"	3/4"	95966A332 3.62	1 1/4"	95966A437 4.51		Hex Size: 7/8"		Hex Size: 7/8"
3/8"	95966A211 \$3.42	7/8"	95966A339 3.69	1 3/8"	95966A441 4.58		Hex Size: 1"		Hex Size: 1"
7/16"	95966A216 3.56						Hex Size: 1 1/4"		Hex Size: 1 1/4"

Retainers

Hold screws captive in panels with these 18-8 stainless steel retainers. They also let you quickly remove the panel without losing the screw.



Screw Size	ID	OD	Thick.	Pkg. Qty.	Per Pkg.	Screw Size	ID	OD	Thick.	Pkg. Qty.	Per Pkg.
4-40	0.093"	0.171"	0.010"	25	91065A620 \$8.97	1/4"-20	0.204"	0.312"	0.012"	25	91065A740 \$8.97
6-32	0.112"	0.171"	0.010"	25	91065A640 8.97	M3	2.4 mm	4.4 mm	0.25 mm	25	91065A810 10.26
8-32	0.146"	0.312"	0.012"	25	91065A660 8.97	M3.5	2.9 mm	4.4 mm	0.25 mm	25	91065A830 10.26
10-24	0.166"	0.312"	0.012"	25	91065A680 8.97	M4	3.8 mm	8 mm	0.32 mm	25	91065A850 10.26
10-32	0.166"	0.312"	0.012"	25	91065A720 8.97						

* Prices are 15% lower when you buy in multiples of five.