

# DC/DC CONVERTERS

## 28 VOLT INPUT

**SLH SERIES**  
**1.5 WATT**

### FEATURES

- Fully qualified to Class H or K
- Radiation hardened
- -55°C to +125°C operation
- 16 to 40 VDC input voltage range
- Fully isolated
- Magnetic feedback
- Variable operating frequency
- Topology – Self Oscillating Flyback
- Inhibit function
- Indefinite short circuit protection



MODELS	
VDC OUTPUT	
SINGLE	DUAL
3.3	±5
5	±12
12	±15
15	

Size (max.): 0.975 x 0.800 x 0.270 inches (24.77 x 20.32 x 6.86 mm)  
See Section B8, case A2, for dimensions.  
Weight: 12 grams max.  
Screening: Standard, Class H, or Class K (MIL-PRF-38534)  
Radiation hardness levels O, L, and R  
See Section C2 for screening and radiation hardness options, see Section A5 for ordering information.

### DESCRIPTION

With a miniature footprint of just 0.8 square inches, the SLH Series™ of 28 V DC/DC converters delivers 1.5 watts of output power while saving significant board area. The wide input voltage range of 16 to 40 VDC accepts the varying voltages of space, military, or aerospace bus power and tightly regulates output voltages to protect downstream components. Single output models feature outputs of 3.3, 5, 12, or 15 volts, and dual output models feature outputs of ±5, ±12 and ±15 volts.

### SCREENING AND REPORTS

SLH converters offer three screening options – Standard, Class H, or Class K – and three levels of radiation hardness. See Section C2, Quality Assurance, pages C2-7 through C2-9, for descriptions. Detailed reports on product performance are also available and are listed on page C2-9.

### CONVERTER DESIGN

SLH Series DC/DC converters incorporate a flyback topology with a variable frequency of approximately 370 kHz. Feedback provides output voltage regulation. Output voltage is magnetically fed back to the input side of the PWM to regulate output voltage. Regulation is also affected by the load.

Dual models regulate the negative output with magnetic coupling to the positive output. Up to 80% of the load may be on one output providing that the other output carries a minimum of 20% of the total load. The dual models can be used as a single output voltage by

connecting the load between positive and negative outputs, leaving the common unconnected resulting in double the output voltage. (ex: SLH2805D can be used as a 10 VDC output.)

When used with Interpoint's STF filter, the combination will meet the requirements of MIL-STD-461C, CE03.

### INHIBIT FUNCTION

When an open collector TTL logic low is applied to the inhibit terminal, pin 7, the converter shuts down and lowers the output voltage to near zero and input current to as low as 5 mA. Leaving the terminal open or applying an open collector TTL logic high will enable the converter.

### PROTECTION FEATURES

All models include a soft-start function to prevent large current draw and minimize overshoot. The converters provide short circuit protection (by restricting the current) and output overload protection.

### CONVENIENT PACKAGING

The SLH Series converters are packaged in hermetically sealed metal cases which provide EMI/RFI shielding.

**For more information, contact your Interpoint representative listed in Section A5.**


**CRANE**

**interpoint**  
A CRANE CO. COMPANY




All technical information is believed to be accurate, but no responsibility is assumed for errors or omissions. Interpoint reserves the right to make changes in products or specifications without notice. SLH Series is a trademark of Interpoint. Copyright © 1999 Interpoint. All rights reserved.

B1-10

# CASE A



# CASES



Note: Although every effort has been made to render the case drawings at actual size, variations in the printing process may cause some distortion. Please refer to the numerical dimensions for accuracy.

## SPACE PRODUCTS

ELEMENT EVALUATION TEST PERFORMED (COMPONENT LEVEL)	STANDARD (O)		CLASS H		CLASS K	
	M/S	P	M/S	P	M/S	P
Element Electrical	yes	no	yes	yes	yes	yes
Element Visual	no	no	yes	yes	yes	yes
Internal Visual	no	no	yes	no	yes	no
Temperature Cycling	no	no	no	no	yes	yes
Constant Acceleration	no	no	no	no	yes	yes
Interim Electrical	no	no	no	no	yes	no
Burn-in	no	no	no	no	yes	no
Post Burn-in Electrical	no	no	no	no	yes	no
Steady State Life	no	no	no	no	yes	no
Voltage Conditioning /Aging	no	no	no	no	no	yes
Visual Inspection	no	no	no	no	no	yes
Final Electrical	no	no	yes	yes	yes	yes
Wire Bond Evaluation*	no	no	yes	yes	yes	yes
SEM	no	no	no	no	yes	no
SLAM™/C-SAM: Input capacitors only (Add'l test, not req. by H or K)	no	no	no	yes	no	yes

Notes

- M/S Active components (Microcircuit and Semiconductor Die)
- P Passive components
- \* Not applicable to EMI filters that have no wirebonds

Definitions

Element Evaluation: Component testing/screening per MIL-STD-883 as determined by MIL-PRF-38534

SEM: Scanning Electron Microscopy

SLAM™: Scanning Laser Acoustic Microscopy

C-SAM: C - Mode Scanning Acoustic Microscopy

Applies to the following products:

SMFLHP Series

SMFL Series

SMHP Series (O&H only)

SMTR Series

SSP Series

SMHF Series

SMSA Series

SLH Series

SLIM Module

SFME120 EMI Filter

SFME28 EMI Filter

SFCS EMI Filter

SFMC EMI Filter

STF EMI Filter

**CRANE**

**interpoint**

A CRANE CO. COMPANY

## QA SCREENING SPACE PRODUCTS

ENVIRONMENTAL SCREENING TEST PERFORMED (END ITEM LEVEL)	STANDARD (O)	CLASS H	CLASS K
Non-destruct bond pull* Method 2023	no	no	yes
Pre-cap inspection Method 2017, 2032	yes	yes	yes
Temperature cycle Method 1010, Cond. C	yes	yes	yes
Constant acceleration Method 2001, 3000 g	yes	yes	yes
PIND Test Method 2020, Cond. B	no	no	yes
Radiography Method 2012	no	no	yes
Pre burn-in test	yes	yes	yes
Burn-in, Method 1015, 125°C			
96 hours	yes	no	no
160 hours	no	yes	no
2 x 160 hour (includes mid BI test)	no	no	yes
Final electrical test MIL-PRF-38534, Group A	yes	yes	yes
Hermeticity test			
Fine Leak, Method 1014, Cond. A	yes	yes	yes
Gross Leak, Method 1014, Cond. C	yes	yes	yes
Final visual inspection Method 2009	yes	yes	yes

Test methods are referenced to MIL-STD-883 as determined by MIL-PRF-38534.

### Note

\* Not applicable to EMI filters that have no wirebonds.

Applies to the following products:

SMFLHP Series	SMHF Series	SFME28 EMI Filter
SMFL Series	SMSA Series	SFCS EMI Filter
SMHP Series (O&H only)	SLH Series	SFMC EMI Filter
SMTR Series	SLIM Module	STF EMI Filter
SSP Series	SFME120 EMI Filter	

# QA SCREENING SPACE PRODUCTS

## RADIATION HARDNESS LEVELS FOR DC/DC CONVERTERS AND LINE INPUT MODULES<sup>1</sup>

PRODUCT LEVEL AVAILABILITY  RADIATION HARDNESS LEVELS	ENVIRONMENTAL SCREENING LEVELS		
	STANDARD (O)	CLASS H	CLASS K
<b>O:</b> Standard, no radiation guarantee For system evaluation, electrically and mechanically comparable to H and K level.	OO	HO	Not available
<b>L:</b> Radiation hardened – Tested lots Up to 50 k Rads (Si) total dose No SEU guarantee	Not available	HL	KL
<b>R:</b> Radiation hardened – Tested lots Up to 100 k Rads (Si) total dose SEU guarantee up to 40 MeV	Not available	HR	KR

L and R are referenced to MIL-PRF-38534, appendix G, Radiation Hardness Assurance (RHA) levels.

**Note**

1. Interpoint's **EMI filters** are designed exclusively with passive components providing maximum tolerance for space environment requirements.

Applies to the following products:

- |                                     |                     |
|-------------------------------------|---------------------|
| SMFLHP Series (levels O and L only) | SMHF Series         |
| SMFL Series (levels O and L only)   | SMSA Series         |
| SMTR Series                         | SLH Series          |
| SSP Series                          | SLIM Series Modules |

**REPORTS: INCLUDED WITH PURCHASE OF PRODUCT HL, KL, HR, or KR**

1. Radiation Susceptibility Analysis
2. Electrical/Thermal Stress Analysis and Derating Report
3. MTBF Report
4. FMEA Report

**OO** option: Select reports available as separate purchases.